



## DOWNLIGHT RECESSED

## CCT FLASH



Flood single lamp



Low Luminance single lamp




Recessed downlight for horizontal mount compact fluorescent lamps with rapid mounting system to false ceiling by means of 'one-touch' spring clips. Ideally suited for indoor application.

Features include:  
White polycarbonate body and bezel.

Polycarbonate reflector with scratch proof formula and 99.9% pure aluminium deposited in high vacuum in specular finishing.


TARI 1 - Luminous distribution  
Single lamp: transverse 2x46°, axial 2x44°. Efficiency 59%.  
Double lamp: transverse 2x62°, axial 2x60°. Efficiency 67%.

TARI 2 - Luminous distribution  
Single lamp: transverse 2x38°, axial 2x37°. Efficiency 57%.  
Double lamp: transverse 2x37°, axial 2x42°. Efficiency 60%.



ART NO	LAMP	LAMP	DIMENSIONS			
	POWER	HOLDER	A (mm)	B (mm)	C (mm)	Hole Ø
54001	2X13W FSM	GX24d/q	225	100	-	215
54000	1X18W FSM	GX24d/q	185	100	-	175
54004	2X18W FSM	GX24d/q	225	100	-	215
54008	1X26W FSM	GX24d/q	185	100	-	175
54003	2X26W FSM	GX24d/q	225	100	-	215
54014	1X32W FSM	GX24q-3	185	100	-	175
54018	1X42W FSM	GX24q-4	185	100	-	175

Note: Subjected to +/-1.5mm  
Specification subject to changes without prior notice



ART NO	LAMP	LAMP	DIMENSIONS			
	POWER	HOLDER	A (mm)	B (mm)	C (mm)	Hole Ø
54002	1X18W FSM	GX24d/q	225	185	-	215
54006	2X18W FSM	GX24d/q	265	200	-	250
54010	1X26W FSM	GX24d/q	225	185	-	215
54012	2X26W FSM	GX24d/q	265	200	-	250
54016	1X32W FSM	GX24q-3	225	185	-	215
54022	1X42W FSM	GX24q-4	225	185	-	215

Note: Subjected to +/-1.5mm  
Specification subject to changes without prior notice

Gear ordering guide: 54001##  
Electromagnetic Ballast: EM  
High frequency electronic ballast: HF  
High frequency dimmable ballast: D  
Emergency Power pack: PP